



# **Data sheet**

## Hydraulic data

Maximum operating pressure PN	6 bar
Discharge port	G 1
Min. fluid temperature $T_{\min}$	5 °C
Max. fluid temperature $T_{\rm max}$	35 °C
Min. ambient temperature $T_{\min}$	0 °C
Max. ambient temperature $T_{\sf max}$	40 °C

#### Motor data

Mains connection	1~230 V, 50 Hz
Voltage tolerance	±10 %
Shaft power P2(Q=max.) of selected impeller * number of pumps <i>NO VALUE</i>	1100 W
Rated power P <sub>2</sub>	1.1 kW
Rated current $I_N$	7 A
Rated speed <i>n</i>	2850 1/min
Insulation class	F
Protection class	IPX4

#### Materials

Pump housing	Grey cast iron
Impeller	Stainless steel
Shaft	Steel
Shaft seal	BQ1PFF
Gasket material	NBR


## **Installation dimensions**

Pipe connection on the suction side <i>DNs</i>	
Pipe connection on the discharge side <i>DNd</i>	G 1



# **Dimensions and dimensions drawings**

## **Wilo-INITIAL JET 9-4**



## **Tender text**

Self-priming single-stage jet pump for water supply, irrigation and rainwater utilisation. Self-priming up to 8

#### **Materials**

Pump housing	Grey cast iron
Shaft	Steel
Shaft seal	BQ1PFF
Gasket material	NBR
Impeller	Stainless steel

## **Operating Data**

Min. fluid temperature $T_{\min}$	5 °C
Max. fluid temperature $T_{\rm max}$	35 °C
Maximum operating pressure <i>p</i>	6.0 bar
Discharge port	G 1
Max. ambient temperature $T_{\rm max}$	40 °C

m. Electrical connection via a terminal box. All parts that come into contact with fluids are corrosion-resistant.

#### Motor data

Mains connection	1~230 V, 50 Hz
Voltage tolerance	±10 %
Rated power P <sub>2</sub>	1.1 kW
Rated current $I_N$	7 A
Rated speed <i>n</i>	2850 1/min
Insulation class	F
Protection class	IPX4

## **Installation dimensions**

Pipe connection on the suction side <i>DNs</i>	
Pipe connection on the discharge side <i>DNd</i>	G 1

## **Ordering information**

Net weight, approx. m	28.9 kg
Brand	Wilo
Product description	Initial JET 9-4
Article number	4186041



# **Installation type**

In inlet mode	
Wall bracket	
Wall bracket	4027328
Shut-off valve	
Ball valve Rp 1	2663980
In suction mode	
Wall bracket	
Wall bracket	4027328
Shut-off valve	
Ball valve Rp 1	2663980
Foot valve	
Foot valve R 11/4	2502408
In suction mode with floating intake	
Wall bracket	
Wall bracket	4027328
Shut-off valve	
Ball valve Rp 1	2663980
Suction/pressure hose kit	
Suction/pressure hose 1¼" SE, PN 10, 1.5 m (cpl.)	2025973
Suction/pressure hose 1¼" SE, PN 10, 10.0 m (cpl.)	2025976
Suction/pressure hose 1¼" SE, PN 10, 15.0 m (cpl.)	2025977
Suction/pressure hose 1¼" SE, PN 10, 3.0 m (cpl.)	2025974
Suction/pressure hose 1¼" SE, PN 10, 5.0 m (cpl.)	2025975
Coarse suction filter (floating extractor)	
Coarse suction filter GR	2024960

## In suction mode with suction hose

Fine suction filter (floating extractor)

Fine suction filter FR

2024962



Wall bracket	
Wall bracket	4027328
Shut-off valve	
Ball valve Rp 1	2663980
Suction hose set	
Suction hose set G1, 7 m	4027874
Suction hose set G1¼, 7 m	4056081



# **Mechanical accessories**

Fittings	
Foot valve	
Footvalve R 11/4	2502408
Non-return valve	
Non-return valve RV/S R 1	2660842
Shut-off valve	
Ball valve Rp 1	2663980
Hoses / hose joints	
Suction hose set	
Suction hose set G1, 7 m	4027874
Suction hose set G1¼, 7 m	4056081
Suction/pressure hose kit	
Suction/pressure hose 1¼" SE, PN 10, 1.5 m (cpl.)	2025973
Suction/pressure hose 11/4" SE, PN 10, 3.0 m (cpl.)	2025974
Suction/pressure hose 11/4" SE, PN 10, 5.0 m (cpl.)	2025975
Suction/pressure hose 11/4" SE, PN 10, 10.0 m (cpl.)	2025976
Suction/pressure hose 1¼" SE, PN 10, 15.0 m (cpl.)	2025977
Suction filter	
Coarse suction filter (floating extractor)	
Coarse suction filter G	2024959
Coarse suction filter GR	2024960
Fine suction filter (floating extractor)	
Fine suction filter F	2024961
Fine suction filter FR	2024962
Valves/accessories	
Screwed connection for non-return valve	
Screwed connection for non-return valve DN 32	2660529

# Wall fixation/installation on a base



#### Wall bracket

Wall bracket	4027328
Wall bracket for Wilo-HiControl and Wilo-FluidControl	
Wall bracket for Wilo-FluidControl	4027326



## **Electrical accessories**

## **Pump control**

HiControl 1-EK	4190895
HiControl 1	4190896

# Pump control/accessories

#### Low-water cut-out switchgear kit for domestic water systems

low-water cut-out switchgear kit WMS G 1¼	4204510
low-water cut-out switchgear kit WMS G2	4204512

## **Pressure control**

#### Pressure sensor

Pressure sensor kit, 6 BAR	4048063
Pressure sensor kit, 10 BAR	4048064
Pressure sensor kit, 16 BAR	4048065
Pressure sensor kit, 25 BAR	4048066

#### Pressure sensor for systems

Pressure sensor, 0 - 6 bar	2550660
Pressure sensor, 0 - 10 bar	2550661
Pressure sensor, 0 - 16 bar	2550662
Pressure sensor, 0 - 25 bar	2550663
Pressure sensor, 0 - 40 bar	2550664

#### Sensor kit

Sensor kit	2501886
------------	---------

#### Level control

#### Float switch WA

Float switch WA65 with 5 m cable	503211390
Float switch WA65 with 10 m cable	503211893
Float switch WA65 with 20 m cable	2004431
Float switch WA65 with 30 m cable	2004432
Float switch WA KR1 S with 5 m cable	6082806
Float switch WA KR1 S with 10 m cable	6082807



Float switch WA65 (PSN-X) with 20 m cable	6088843
Float switch WA65 (PSN-X) with 10 m cable	6088844
Float switch WA65 (PSN-X) with 5 m cable	6088845
Float switch WA-EK	
Float switch WAEK 65, 5 m cable	503211698
Float switch WAEK 65, 10 m cable	2005516
Float switch WAEK 65, 20 m cable	2005517
Float switch WAO-EK	
Float switch WAOEK 65, 20 m cable	2005626
Immersion probe	
Submersible electrode, 3 m	500183799
Submersible electrode, 3 m Submersible electrode, 4 m	500183799 2516278
Submersible electrode, 4 m	2516278
Submersible electrode, 4 m Submersible electrode, 5 m	2516278 500937990
Submersible electrode, 4 m Submersible electrode, 5 m Submersible electrode, 10 m	2516278 500937990 2501937
Submersible electrode, 4 m  Submersible electrode, 5 m  Submersible electrode, 10 m  Submersible electrode, 20 m	2516278 500937990 2501937 2516283
Submersible electrode, 4 m  Submersible electrode, 5 m  Submersible electrode, 10 m  Submersible electrode, 20 m  Submersible electrode, 25 m	2516278 500937990 2501937 2516283 2000601
Submersible electrode, 4 m  Submersible electrode, 5 m  Submersible electrode, 10 m  Submersible electrode, 20 m  Submersible electrode, 25 m  Submersible electrode, 30 m	2516278 500937990 2501937 2516283 2000601 2514045
Submersible electrode, 4 m  Submersible electrode, 5 m  Submersible electrode, 10 m  Submersible electrode, 20 m  Submersible electrode, 25 m  Submersible electrode, 30 m  Submersible electrode, 35 m	2516278 500937990 2501937 2516283 2000601 2514045 2516284



#### **Services**

With Wilo as your partner, you can not only be sure of choosing high-quality product solutions, but also of benefiting from a comprehensive, worry-free package of well thought-out services. We collaborate to develop a service concept tailored to your individual needs; with our expertise and personal consultancy, we make sure that the operation of your systems is as energy-efficient, reliable and economical as possible. All the while our competent Wilo service technicians are ready to assist you with fast, reliable and on-time support.

#### **Recommended services**

Wilo-Live Assistant Service	2216415

#### More suitable services

Service Package L FWJ/HiMulti 3-5	2219704
Service Package M FWJ/HiMulti 3-5	2219675
Supervision FWJ/HiMulti 3-5	2219328
Installation FWJ/HiMulti 3-5	2219363
Commissioning FWJ/HiMulti 3-5	2219394
Maintenance BASIC FWJ/HiMulti 3-5	2219534
Maintenance COMFORT FWJ/HiMulti 3-5	2219496
Maintenance PREMIUM FWJ/HiMulti 3-5	2219549
System Optimisation FWJ/HiMulti 3-5	2219258
Energy Solutions FWJ/HiMulti 3-5	2219293
Repair FWJ/HiMulti 3-5	2219617