



Abbildung ähnlich


Data sheet

Technical data

Line type	twisted in pairs, shielded
Line length	900 m (bus topology with max 3 m spur line); 500 m (free topology, max. 250 m between communicating consumers)
Spur line	max. 3 m
Terminal cross-section	1,5 mm ²
Interface	TP/FT10
Speed	78 kBit/s, constant
Format	-
Protocol	LonMark Layers 1-6 Interoperability Guidelines 3.2
Profile	LonMark pump controller 8210

Ordering information

Product data

Brand	Wilo
Product description	CIF-Module LON
Article number	2190370 
EAN number	4048482802749
Colour	Black
Minimum order quantity	1
Date of sales availability	2018-11-01

Packaging

Packaging type	Cardboard box
Packaging property	Sales packaging
Pieces per pallet	1
Number per layer	1

Dimension, weight

Length with packaging	200 mm
Length <i>L</i>	74 mm
Height with packaging	145 mm
Height <i>H</i>	34 mm
Width with packaging	145 mm
Width <i>W</i>	70 mm
Gross weight, approx. <i>m</i>	0.4 kg
Net weight, approx. <i>m</i>	0.1 kg

Tender text

Interface module as retrofittable plug-in module for extending the communication interfaces of the pump in accordance with various standards and protocol variants according to type key.

General functions

Serial, digital interface for connection to building automation for the transfer of data points as:

- > Control commands to the pump
- > Messages from the pump
- > Process values

Equipment

TP-FT 10 interface with LonTalk protocol

Technical data

Line type	twisted in pairs, shielded
Line length	900 m (bus topology with max 3 m spur line); 500 m (free topology, max. 250 m between communicating consumers)
Spur line	max. 3 m
Terminal cross-section	1,5 mm ²
Interface	TP/FT10
Speed	78 kBit/s, constant
Format	-
Protocol	LonMark Layers 1-6 Interoperability Guidelines 3.2
Profile	LonMark pump controller 8210
Net weight, approx.	0.06 kg
Make	Wilo
Item no.	2190370

Information about the download

<http://www.wilo.de/automation> (German)

<http://www.wilo.com/automation> (English)

Scope of delivery

- > CIF module
- > 2x M16x1.5 threaded cable glands (only suitable for Stratos MAXO)
- > Installation and operating instructions

Bus lines (shielded!) must be provided by the customer